

**30T Amphibious Excavator**



**Specifications**

Amphibious excavator has two configurations:  
 30T Amphibious machine or  
 With additional side and centre pontoons and 10m hydraulic spuds.  
 Excavator can operate on all terrains including unsuitable ground for conventional machines and  
 operate in varying water depths of 0-10m unassisted  
 Both configurations come with GPS and various attachments

<b>30T Amphibious Machine</b>	
Track length:	10.76m
Track width:	6.5m
Buoyancy:	
Unassisted operating depth:	0-2m
Approx weight:	
<b>30T Amphibious machine with additional sides, centre pontoons and 4x 10m hydraulic spuds</b>	
Track length:	10.76m
Side pontoon width:	6.5m
Overall Width:	10.76
Buoyancy:	
Unassisted operating depth:	0-10m
Stability increased by:	10 Times
Approx weight:	67T



Image shows amphibious configuration with additional sides, centre pontoons and rear 10m hydraulic spud

Working radius 4 - 18m depending on attachments			
Bulking bucket 1.5m <sup>3</sup>	Muller vibrator hammer	6m Long reach Extension	Demolition processor
Tilt bucket 2m <sup>3</sup>	65 kN Auger Drive	2.5m Extension	1.5m <sup>3</sup> Concrete Skip
Rotating Rock/Block Grab	4m Crane extension	DX25 drop hammer	Movax SP60 Vibrator
PVE 2319 vibratory hammer	Tilt rotator	Pulveriser	





